







# IAM YOUR HOLIDAY HIGHLIGHTS

## COOLPIX S33

If you have an active lifestyle, you'll adore the ready-foranything COOLPIX S33 for its bright styling, ease of use and reliable performance under tough conditions – waterproof<sup>1</sup> to 10, shockproof<sup>2</sup> to 1.5m, cold resistant to -10°C and dustproof<sup>3</sup>. The 3x optical zoom extends to 6x Dynamic Fine Zoom<sup>4</sup> for close-ups, and smooth Full HD movies come at the touch of a button. Underwater face framing can capture portraits without even having to get in the water. Adult and child menus make the COOLPIX S33 easy for everyone to use, while Scene modes and a choice of colourful bodies make shooting fun – every time!



White



Blue





Note: Color availability may vary per region.



www.europe-nikon.com

### Reliable, Easy-To-Use and Waterproof

#### **Tough and reliable**

Take it with you everywhere: it's dustproof, waterproof to 10m, cold resistant to -10°C and shockproof to 1.5m. Be adventurous with a camera that can take the knocks.

### Adult and child menus

Variety menu defaults to an easy child menu and it's simple to switch to an adult menu. There's no need for a special children's camera - this one's for all the family!



**Recommended accessories** 



#### 13.2 effective megapixels

With a CMOS sensor that makes the most of its megapixels, clear photos with sharp details are guaranteed - ideal for enlargements you'll want to frame or turn into posters.





#### Underwater face framing

Shoot underwater portraits without getting in the water! Face framing technology automatically detects faces and releases the shutter, so you can snap portraits and stay dry.

#### Other features

- NIKKOR 3x optical zoom lens
- Target finding AF incorporated
- 6.7-cm/2.7-in 230k-dot LCD monitor Shoot a movie miniature
- Motion blur reduction
- Easy to handle



**NIKON Floating Strap** ALM23060

#### **Nikon COOLPIX S33 Specifications**

Effective pixels	13.2 million*1
Lens	NIKKOR lens with 3× optical zoom, 4.1–12.3 mm (35mm [135] format equivalent: 30–90 mm), f/3.3–5.9
Digital zoom magnification	Up to 4× (35mm [135] format equivalent: approx. 360 mm)
Focus range <sup>*2</sup>	[W]: Approx. 5 cm (2 in.)—∞, [T]: Approx. 50 cm (1 ft 8 in.)—∞
Monitor	6.7 cm (2.7-in.), approx. 230k-dot, TFT LCD with antireflection coating and 5-level brightness adjustment
Storage media	Internal memory (approx. 25 MB), SD/SDHC/SDXC memory card <sup>+3</sup>

ISO sensitivity (Standard output sensitivity)*4	ISO 125–1600
Power sources	One Rechargeable Li-ion Battery EN-EL19 (included), AC Adapter EH-62G (available separately)
Battery life*5	Approx. 220 shots with EN-EL19 battery
Dimensions (W x H x D)	Approx. 109.5 $\times$ 67.0 $\times$ 37.6 mm excluding projections <sup>*6</sup>
Weight	Approx. 180 g (6.3 oz) with battery and memory card <sup>6</sup>

- Image processing may reduce the number of effective pixels. All distances measured from center of front surface of the protective glass. Not compatible with Multi Media Cards (MMC). Depending on the conditions, certain settings may not be configured. Based on CIPA industry standard for measuring life of camera batteries. Measured at 23°C (+/-3°C); zoom adjusted with each shot, built-in flash fired with every other shot, image mode set to Normal. In a cold environment, the number of shots may decrease according to the battery characteristics. Method of noting dimensions and weight is in accordance with CIPA DCG-002-2012 guideline.

Note: Full HD refers to this camera's ability to record movies in 1920 x 1080 format

- The camera is equivalent to JIS/IEC waterproof class 8 (IPX8) and JIS/IEC dustproof class 6 (IP6X).
  This camera has passed Nikon's in-house test (drop test from a height of 1.5 m/5 ft on a 5 cm/2 in. thick plywood panel) compliant with MIL-STD 810F Method 516.5-Shock (U.S. Department of Defense test method standard).
  The camera is equivalent to JIS/IEC waterproof class 8 (IPX8) and JIS/IEC dustproof class 6 (IP6X).
  Dynamic Fine Zoom can zoom 2x further than the longest optical telephoto range, while maintaining provide the complexity of the complex
- maximum image resolution.

The SDXC logo is a registered trademark of SD-3C, LLC in the United States and/or other countries. PictBridge is a trademark. Products and brand names are trademarks or registered trademarks of their respective companies. Sample images shown in this leaflet are simulated.





WARNING TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



